

Instructions

Use of haid-tec PolyPlusPad



PolyPlusPads can be used both manually and with a cleaning machine.
The following points must be considered:

- Do not apply haid-tec PolyPlusPads dry!
- The white-turquoise side of the pads should face towards the floor covering.
- Do not use on extremely sensitive surfaces (e.g., high-gloss plastics, high-gloss painted surfaces, etc.).
- Test in an inconspicuous area before application (follow the floor manufacturer's recommendations)

Mount haid-tec PolyPlusPads on suitable drive plates of the machine:

- **Single-disc machines** - Use machines with up to 350 revolutions per minute - not suitable for high-speed machines
- **Scrubber-dryers** - Use of an inner hole holder is recommended
- **Orbital machines** - Use PolyPlusPads with velcro backing
- **Eccentric machines** - Use PolyPlusPads with velcro backing

With the **fine polyester active fibers** with a pile height of approximately 8-10mm, the **PolyPlusPads** reach into the smallest recesses and surface structures. **The pads achieve good mechanical cleaning performance** on various mineral and resilient floor coverings, such as porcelain stoneware, natural stones, textured tiles, vinyl, linoleum, rubber stud coverings, and many more.

Unlike conventional microfiber pads, the **PolyPlusPads self-rinse during use – the fibers do not clog with dirt.** The PolyPlusPads can be used in maintenance cleaning without washing until the Poly-Active fiber is completely worn out.

For hygienically sensitive areas (e.g., hospital cleaning), the PolyPlusPads **can be machine-washed** several times up to 60°C. Do not use fabric softener and only dry at low temperatures.

The PolyPlusPads are **high-quality**, reinforced in the heavily stressed edge area with binding tape and sewn with a stitched seam.

When used with scrubber-dryers, depending on the floor covering, stand times of **up to 100,000 square meters or more per pad** are possible. **Alternating use with MelaminPlusPads can help avoid costly deep cleaning.**



haid-tec
geprüfte Oberflächentechnik GmbH
Riedstraße 10
D-89616 Rottenacker
T: +49 7393 / 918 39 10
F: +49 7393 / 918 39 19
E: info@haid-tec.de
www.haid-tec.com
shop.haid-tec.com/